BRADFORD WHITE OIL-FIRED WATER HEATERS

Bradford White
Areo Series Residential Energy Saver Oil-Powered Hot Water Heaters

NOTE: Purchase burners separately. See below.

BRADFORD WHITE®

FEATURES:

- 1" non-CFC foam insulation covering the sides and top to slow heat loss. Also increases jacket rigidity.
- Low operating cost allows homeowners to cut costs by as much as 60%.
- Stainless steel baffle to resist corrosion.
- High recovery rate – 3 to 4 times fast than other methods.
- Hydrojet® Total Performance System reduces cold inlet sediment build-up. Also increases 1st hour hot water delivery and minimizes temperature build-up at the top of the tank.
- Vitraglas® lined tank with ceramic porcelain-like coating resists corrosion and provides a tough interior surface for long life.
- T&P valve relief valve opening comes standard with special side tapping on the side of the tank.
- Brass drain valve.
- Two protective magnesium anode rods to neutralize the corrosive effect of water chemicals, fight rust and assure long tank life.
- Warranty: 6 years on tank, two years on parts.

Cap. Gal.	Min/Max Firing GPH	Max. Recovery Rate GPH	Air Tube	Flue	Water Conn.	Height x Dia.	Floor to Flue Center	Mfr#	Item#	Price
AREO RESIDENTIAL SEREIS										
WITH T&P VALVE, 3/4" DRAIN VALVE CONNECTION, 300 / 150 PSI TEST WORKING PRESSURE										
32	.65 / .75	102	5-1/2"	6"	3/4"	51-1/2" x 20-1/2"	– – –	CF-32-6	CF326	$1,096.20
50	.75 / .85	97 / 114	7	6"	3/4"	62" x 23-1/2"	– – –	CF-50-6	CF506	1,588.10
30	.85	116	7"	6	3/4"	49-1/2" x 23-1/2"	49"	RF-30-6	RF306	1,200.20
50	1.25 / 1/35	184	7-1/2"	7	1-1/4"	68-1/2" x 26-1/2"	61"	RF-50-6	RF506	1,855.12
AERO COMMERCIAL SERIES										
70	.85	115	– – –	8"	3/4"	64' x 24"	– – –	CF-70-3	CF703	2,616.86
OIL BURNERS FOR AREO SERIES SOLD SEPARATELY										
Beckett burner with dual aquastat for CF-32-6								228-44392-01		694.26
Beckett burner with dual aquastat for CF-50-6								228-44392-03		694.26
Beckett burner with dual aquastat for RF-30-6								228-44392-07		867.82
Beckett burner with dual aquastat for RF-50-6								228-44392-09		867.82

NOTE: Firing and recovery rates are at 100°F.

CF = Center flue, **RF** = Rear flue.